

## Telephone Transponder



Part # 1302034

*Provides room temperature set back signals to Steffes 2100, 2000 and/or 1000 series room units through telephone communication.*

- ◆ Interfaces with a touch tone phone, with or without answering machine
- ◆ 120V plug-in cord
- ◆ Programmable to suit personal needs, including security
- ◆ Local or remote operation
- ◆ User-friendly, easy to use
- ◆ Interfaces with most room thermostats equipped with a telephone interface

## Remote Room Temperature Sensor

*Provides remote room temperature information to Steffes 2100, 2000 and/or 1000 series room units.*

- ◆ Replaces the heater's built-in room temperature sensor to monitor the temperature at a location in the room other than on the heater
- ◆ Available in configurations that control 1, 2, or 3 heaters simultaneously
- ◆ Direct wired to the heater using low voltage, 2-conductor cable
- ◆ 2 3/4" X 4 1/2" off-white enclosure



Part # 1302024 (1-heater)  
1302041 (2-heater)  
1302042 (3-heater)

## Outdoor Temperature Sensor



Part # 1302033

*Provides outdoor temperature information to Steffes 2100, 2000 and/or 1000 series room units as well as Comfort Plus central systems for automatically regulating brick core temperature.*

- ◆ Can be wired directly to the heater or to a power line carrier control system (CCRP or Transmitter)
  - If direct wired to the heater, one sensor is needed for each heater
  - If direct wired to a PLC control system, only one sensor is needed for the entire application
- ◆ Low voltage, 2-conductor cable
- ◆ Mounting bracket provided or its 1/2" male pipe thread nipple for mounting into a knockout

## Time Clocks


**Theben Brand Device:** *Provides low voltage peak control or room temperature setback signals directly to Steffes 2000 and 1000 series room units and Steffes Power Line Carrier Control systems.*



Part # 1301007R (115V)  
1301008R (230V)

- ◆ Operating Voltage 115V or 230V (specify when ordering)
- ◆ Seven-Day programmable with 28 Memory Locations
- ◆ Automatically adjusts to daylight savings time (if applicable)
- ◆ Override Capability
- ◆ Switching capacity - 10 AMPS/250VAC
- ◆ 4 year Lithium Battery Back-up
- ◆ Easily Installed on Din Rail
- ◆ Can be preprogrammed prior to installation (program and time settings retained for the life of the battery)

**Microprocessor Module:** *Provides peak control signals directly to 2100 series room units and Comfort Plus systems. Also can provide room temperature set back signals to the 2100 series room units.*



Part # 1301014

- ◆ Directly connected to heater's internal control board (one/heater)
- ◆ 5/2 Day programmable
- ◆ Allows up to 3 separate weekday and weekend peak time settings
- ◆ Provides up to 4 separate weekday and weekend room temperature set back time settings (room units only)
- ◆ Capacitor power back-up (3-days)

ONE-YEAR MANUFACTURER'S LIMITED WARRANTY